

620 | 6200



HOT MELT

COLD TEMPERATURE CARTON SEALING TAPE




PRODUCT DESCRIPTION

These cold temperature packaging tapes have been formulated to be used in applications at refrigerated temperatures or at room temperature and then stored in low temperature environments which include produce packaging, dairy facilities, meat and poultry processing plants. Perform very well in cold weather moving /storage conditions and unheated warehouses located in cold weather climates.

PERFORMANCE FEATURES

- Adheres instantly to corrugated, paper, film and a number of surfaces
- Good edge tear and split resistance.
- Aggressive high tack adhesive with excellent holding powers

TECHNICAL SPECIFICATIONS

| | |
|--|---|
| Color: | Clear  |
| Backing (mils/mm): BOPP | 1.16 / 0.029 |
| Adhesive: | Synthetic Rubber and Resins |
| Total Thickness (mils/mm): | 1.85 / 0.047 |
| Adhesion to Steel (oz/in. - N/100mm): | 27 / 29 |
| Tensile Strength (lbs/in. - N/100mm): | 26 / 455 |
| Elongation at Break: | 165% |
| Service Temperature - Min / Max: | -15°F (-26°C) / 100°F (38°C) |
| Application Temperature - Min / Max: | 20°F (-7°C) / 110°F (43°C) |
| Available Widths: | 48mm, 72mm |
| Available Lengths (hand): | 100m |
| Available Lengths (machine): | 914m, 1371m |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Vibac Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

