



1626 Bridgewater Road
Bensalem, PA 19020
Toll Free: 800-331-1373
Fax: 215-245-8554
www.prestotape.com

Technical Data Sheet

35RW40 Heavy Duty Reverse Wound Floor Protection Film

Product Description:

The 35RW40 product is a polyethylene film coated with an inert water-based acrylic adhesive. The product is reverse wound and can be easily applied by hand or with an applicator. This temporary floor protection film provides protection during painting, remodeling, relocations or other high traffic situations. The many variations in floor materials; wood, natural stone, ceramics, etc. and the finishing techniques for each, make it imperative that the user determines its suitability.

Product Properties / Characteristics:

Nominal Results

Adhesion to Steel: PSTC-101 (oz/in)	2.0 to 4.5
Tack Level:	Medium
Tensile Strength: PSTC-131 lb/sq in	11
Elongation (%): PSTC-131	325
Thickness: PSTC-133	3 mils (nominal)

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

Limitations of Warranty: Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. For a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape's option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.