

RENFREW™ 124R

Vinyl Coated Cotton Cloth Tape

DESCRIPTION

Renfrew 124 is a vinyl coated cotton cloth tape that is single coated with 3.75 mils of a natural rubber base pressure sensitive adhesive.

APPLICATIONS

- Outerwrap support tape.

PRODUCT BENEFITS

- High quality water resistant tape with a matte finish vinyl coating.
- Aggressive high tack adhesive formulated for skin contact.
- Absence of liner allows for ease of application.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesive Thickness (Each Side)	3.75 (.95)	Mils (mm)	-
Adhesive Type	Natural Rubber	-	-
Backing Adhesion (PSTC 101 Mod./180°) Initial to Backing Substrate (20 min. @ RT)	15 (41)	Oz/Inch (N/25mm)	-
Draize Skin Irritation	passed	-	-
Peel Adhesion (PSTC 101 Mod./180°) Initial to S.S. (20 min. @ RT)	30 (8.2)	Oz/Inch (N/25mm)	-
Tensile Strength (ASTM D-1000)	640 (175)	-	ASTM D1000
Total Thickness (Not Including Liner)	10.5 (.267)	Mils (mm)	Internal *

STANDARD PRESENTATIONS

RECOMMENDATIONS

Application to Surface: Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE: 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.

2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.