

PRODUCT DESCRIPTION

This double coated polyethylene foam tape is specifically designed for mounting and bonding tasks, both indoors and outdoors. Its unique formulation allows it to adapt and adhere to uneven surfaces, ensuring a reliable bond. This tape exhibits excellent temperature resistance and long-lasting durability, making it suitable for a variety of applications. It provides strong adhesion to numerous plastics and is particularly effective on low-surface energy materials such as aluminum and glass. Commonly utilized in window glazing projects, this tape is designed for fast and easy to use permanent bonding with high strength and long-term durability, delivering high strength and enduring performance.

APPLICATIONS

- Indoor general purpose mounting and joining
- Window glazing
- Automotive mirror bonding
- Decorative trim
- Nameplate mounting
- Point-of-purchase displays and signs

FEATURES & BENEFITS

- High ultimate adhesion to a wide variety of surfaces
- Conformable tape bonds to irregular surfaces



PHYSICAL PROPERTIES

| TECHNICAL PROPERTY | VALUES |
|--------------------|------------------------------------|
| Backing | 0.8mm Polyethylene Foam (67kg/CBM) |
| Adhesive | Acrylic solvent |
| Release Liner | PE liner |
| Total Thickness | 0.8mm (1/32") |
| Initial Tack | ≥30N/25.4mm |
| Holding Power | ≥50 hours |
| Heat Resistance | 20°C ~+ 80°C |
| Core I.D. | 3" (76mm±1) |

STANDARD WIDTHS

¼" up to 42" (6 mm up to 1060 mm)
Custom widths available

STANDARD LENGTH

216 ft (66 m)

AVAILABLE COLOURS

Black

PRODUCT RECOMMENDATIONS

The products should be stored at room temperature, away from moisture and heat sources.

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied is clean, dry, and free from grease and oil.

Users are advised to conduct tests prior to application to ensure the tape's suitability for their specific needs and techniques.

The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.