



## GENERAL PURPOSE TENSILIZED STRAPPING TAPE

### PRODUCT DESCRIPTION

This product is a general purpose tensilized strapping tape is used for packaging, bundling, palletizing, colour-coding and unitizing applications. It is constructed of a tensilized MOPP film with a water-based acrylic adhesive system. This high strength tape is quick to bond to a variety of surfaces. Designed to keep boxes from shifting in transit and reinforces packages bearing significant weight.

### PHYSICAL PROPERTIES

Adhesive:	Water based acrylic
Colour:	Black
Total Thickness:	2.8 mil
Adhesion to Steel:	30.0 to 32.0 oz/in
Tack Level:	High
Tensile Strength:	97 lb/sq in
Elongation:	35%

### STANDARD WIDTHS

12 mm, 18 mm, 24 mm, 48 mm

### STANDARD LENGTHS

55 metres

### RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.



The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.