



A NEKOOSA BRAND

GXP-550

Technical Data

Product Description – A medium tack paper application tape for vinyl graphics used in sign making and surface protection. The product consists of a self-wound, standard grade saturated backing coated with a specially formulated latex pressure sensitive adhesive.

Product Characteristics

| | | |
|--|------------|---|
| Construction | | |
| Backing | | White translucent latex saturated paper |
| Adhesive | | Water based natural latex |
| Total Thickness | | 4 mil (nominal) |
| Performance | | |
| Tensile Strength (pli) | | |
| MD | 20 | |
| Elongation (%) | 2.4 | |
| Adhesion (oz/in) | | |
| 180° Peel @ time of manufacture | | |
| PSTC#4 bright annealed stainless steel | 4.0 - 18.0 | |

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Main Tape assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Main Tape product proven defective. For full disclosure of the Limited Warranty, please contact your Main Tape representative.

Typical Uses - Excellent for medium and large plotter and die-cut graphics. Works well with pre-spaced lettering 2-12", small one piece decals and mid-sized line striping.