

TECHNICAL DATA SHEET

G-3273

ISSUE DATE: 06/05/2014

PRODUCT DESCRIPTION	G-3273 is a synthetic water based adhesive specially designed for laminating and glue up cardboard paper.	
USES	G-3273 is designed as a product for high speed roll coat and other application methods.	
FEATURES	<ul style="list-style-type: none">• Low viscosity• Excellent machinability• Excellent adhesion on a variety of substrates• Excellent fast setting and high wet tack• Excellent low forming	
TYPICAL PROPERTIES	Viscosity (cps):	400 - 600
	Solids (%):	58.0 - 60.0
	Specific Gravity:	1.08
	pH:	4.0 - 5.5
PRODUCT APPLICATION	Recommended for roller or extrusion applicators.	
ADDITIONAL DATA	Color: White	
PACK SIZES	18.9 L pail	220 kg drum
	1,100 kg tote	Weights may vary
STORAGE CONDITIONS	Keep from freezing. Keep away from direct sunlight or heat.	
LIMITATIONS	Shelf Life: Six (6) months when stored as recommended.	

Any recommendations contained herein or any information given by any Dural representative is based on tests and information believed to be accurate. However, since we have no control over the conditions under which our products are transported, stored, handled, or used by purchasers, all recommendations and sales are made on condition that Dural will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. It is the user's responsibility to ensure that this sheet is current prior to using the product.