

2900

Lowry

The Tape Specialists

POLYETHYLENE FILM SURFACE PROTECTION TAPE

PRODUCT DESCRIPTION

This polyethylene surface protection film contains an acrylic adhesive and offers temporary protection to a wide range of surfaces, including metal, plastics and aluminum.

It is also effective in protecting semi-smooth surfaces such as hardwood and ceramic tile floors from dirt, spills, dust, construction debris, and damage. It is resistant to tears and punctures from sharp objects. Ideal for use in high-traffic areas in construction building and renovation projects.

PHYSICAL PROPERTIES

Backing:	LDPE
Colour:	Blue
Adhesive:	Acrylic type with solvent
Total Thickness:	45±5 micron
180°C Peel Strength:	400 g ±10% / 25 mm
Elongation:	≥ 1.0KN/M
Elongation at Break:	≥ 300%
Temperature Resistance:	60°C, 160 hours
	no residue glue after removal
Core I.D.:	3" (76mm±1)

STANDARD WIDTHS

Custom widths available

STANDARD LENGTHS

600 feet (182 metres)

RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.



The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.