

680 | 682 | 6800 | 6802

HOT MELT



## SUPER TACK CARTON SEALING TAPE



### PRODUCT DESCRIPTION

This Super Tack packaging tape is specifically designed for boxes made of recycled fibers. This product has a conformable film backing coupled with a consistent pressure sensitive hot melt adhesive coating.

### PERFORMANCE FEATURES

- Adheres instantly to corrugated, paper, film and a number of surfaces
- Good edge tear and split resistance.
- Aggressive high tack adhesive with excellent holding powers

### TECHNICAL SPECIFICATIONS

<b>Color:</b>	Clear <input checked="" type="checkbox"/> White <input type="checkbox"/>
<b>Backing (mils/mm):</b> BOPP	1.16 / 0.029
<b>Adhesive:</b>	Synthetic Rubber and Resins
<b>Total Thickness (mils/mm):</b>	1.87 / 0.0475
<b>Adhesion to Steel (oz/in. - N/100mm):</b>	57.8 / 63
<b>Tensile Strength (lbs/in. - N/100mm):</b>	26 / 455
<b>Elongation at Break:</b>	165%
<b>Service Temperature - Min / Max:</b>	30°F (-2°C) / 140°F (60°C)
<b>Application Temperature - Min / Max:</b>	50°F (10°C) / 110°F (43°C)
<b>Available Widths:</b>	48mm, 72mm
<b>Available Lengths (hand):</b>	100m
<b>Available Lengths (machine):</b>	914m



Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Vibac Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.