

## PRODUCT DESCRIPTION

This flatback paper tape features vibrant, colourful paper that is coated with a natural rubber adhesive. Its smooth surface, in contrast to creped paper, allows for superior printing quality. The tape is designed for easy unwinding, making it ideal for high-speed printing applications. Additionally, it exhibits strong face-to-face bond strength, making it suitable for various uses such as flexographic printing, colour coding, and identification, with a writable surface for added convenience.

## APPLICATIONS

- **Colour Coding and Identification:** Used to identify, categorize, or highlight items in manufacturing, logistics, or inventory management.
- **Splicing and Tabbing:** Ideal for flying splices in printing, tabbing rolls of paper or film, and core starting.
- **Packaging and Sealing:** Suitable for sealing, bundling, and protecting cardboard boxes, especially where a secure, high-adhesion, or coloured closure is needed.
- **Graphic Arts and Framing:** Utilized in framing for backing, photo edging, and cropping, as well as design and layout work.
- **Masking:** Used for paint masking where a flat, non-crepe edge is required.
- **Printing and Labelling:** Compatible with flexographic inks and easily marked with pens, pencils, or rubber stamps.

## FEATURES & BENEFITS

- **Specifications:** Meets ASTM D6123, Type II; CID A-A-883B, Type II.



## PHYSICAL PROPERTIES

TECHNICAL PROPERTY	VALUES
Backing	Kraft flatback
Adhesive	Natural rubber
Total Thickness	5.8 mils
Tensile Strength	32 lb/in
Adhesion	31 oz/in
Elongation at Break	3%
Core I.D.	3"

## STANDARD WIDTHS

6 mm up to 1448 mm  
Custom widths available

## STANDARD LENGTH

55 m

## AVAILABLE COLOURS

Green, Light Blue, Orange, Red, White and Yellow

## PRODUCT RECOMMENDATIONS

The products should be stored at room temperature, away from moisture and heat sources.

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied is clean, dry, and free from grease and oil.

Users are advised to conduct tests prior to application to ensure the tape's suitability for their specific needs and techniques.

The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.