

830 | 831 | 8300 | 8301

HOT MELT



SUPERIOR PERFORMANCE CARTON SEALING TAPE



PRODUCT DESCRIPTION

This Superior Performance packaging tape was designed for carton sealing, splicing, bundling, and other ultra demanding packaging applications. It offers super strength adhesive power in the heaviest applications.

PERFORMANCE FEATURES

- Adheres instantly to corrugated, paper, film and a number of surfaces
- Good edge tear and split resistance.
- Aggressive high tack adhesive with excellent holding powers

TECHNICAL SPECIFICATIONS

Color:	Clear <input type="checkbox"/> Tan <input checked="" type="checkbox"/>
Backing (mils/mm): BOPP	1.97 / 0.050
Adhesive:	Synthetic Rubber and Resins
Total Thickness (mils/mm):	2.83 / 0.072
Adhesion to Steel (oz/in. - N/100mm):	56 / 60
Tensile Strength (lbs/in. - N/100mm):	45 / 787
Elongation at Break:	200%
Service Temperature - Min / Max:	30°F (-2°C) / 140°F (60°C)
Application Temperature - Min / Max:	50°F (10°C) / 110°F (43°C)
Available Widths:	36mm, 48mm, 72mm, 96mm, 144mm
Available Lengths (hand):	50m, 55m, 100m
Available Lengths (machine):	914m

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Vibac Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

